

VIRAJ H20

divinity lights



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable White 2700K-6500K

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI +

SDCM ≤ 3

PMMA Diffuser

L70 @ 50,000h


Aluminium

Types



Pendant/ Surface/ Recessed

Single Line Diagram

Pendant/ Surface



Recessed



VIRAJ H20

Viraj H20 sleek and slim linear fixture has:


- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency PMMA Diffuser
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap- fit system
- No visible screw
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

Colours



Light Distribution

Direct



CRI ≥ 90



TUNABLE WHITE

VIRAJ H20



VIRAJ H20 (DIRECT)

Product Order Code	System Power	Dimensions
1035-  1	5W	L = 300mm W = 22mm, H = 25mm
1035-  2	10W	L = 600mm W = 22mm, H = 25mm
1035-  3	15W	L = 900mm W = 22mm, H = 25mm
1035-  4	20W	L = 1200mm W = 22mm, H = 25mm
1035-  5	40W	L = 2400mm W = 22mm, H = 25mm

Order Options

Distribution

Direct

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4



CRI	
>90	1

Beam Angle

110°

Control		
ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5

Mounting Type

Pendant	1
Surface	2
Recessed	

Material Colour

Black		1
White		2
Grey		3

Accessories

Product Order Code	Accessories Name	Accessories Image
1035-01 	LED PCB	
1035-02	Suspension Wire	
1035-03	PMMA Diffuser	
1035-04	Profile Connector	
1035-05 	Profile Endcap	

Order Options

CCT (Colour Temperature) 

3000K

4000K

5700K

Tunable White 2700K-6500K 

1

2

3

4

CRI 

>90

1

Material Colour 

Black

White

Grey







1

2

3