

# XTO LINEAR

divinity lights



XTO LINEAR LENS



Lens

Micro Prismatic Diffuser

XTO LINEAR LENS + DIFFUSER



# divinity lights

## Quick Info

CRI ≥ 80/ 90/ 95

3000K/ 4000K/ 5700K/ 6500K

Tunable White 2700K-6500K

Up to 100lm/W

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 / DALI-2 DT8 / D4i / DALI +

POE (Power Over Ethernet)

SDCM<3

Lens

L70 @ 50,000h


Aluminium

## Types


Pendant/ Surface

## Single Line Diagram


XTO 20




XTO 25




XTO 30






XTO 35



XTO 40



XTO 45



## XTO LINEAR

XTO Linear has :


- Luminaire housing of extruded aluminium
- Range of size/angle design solutions
- Surface powder coated
- LED PCB mounted on insert design with heat sink
- Bottom opening for easy maintenance
- Modular design concept
- UGR less than 16
- Micro-structure & anti-glare optical lens design
- Uniform illumination
- Energy-efficient LED with color rendering

## Colours



## Light Distribution

Direct Direct-Indirect



CRI ≥ 80/ 90/ 95



TUNABLE  
WHITE

## XTO LINEAR



### XTO LINEAR ( DIRECT )

Product Order Code	System Power	Dimensions
1018-1[icon][icon][icon][icon][icon]81	8W	L = 300mm
1018-1[icon][icon][icon][icon][icon]82	16W	L = 600mm
1018-1[icon][icon][icon][icon][icon]83	24W	L = 900mm
1018-1[icon][icon][icon][icon][icon]84	35W	L = 1200mm
1018-1[icon][icon][icon][icon][icon]85	70W	L = 2400mm

### XTO LINEAR ( DIRECT-INDIRECT )

Product Order Code	System Power	Dimensions
1018-▼[icon][icon][icon][icon][icon]81	15W	L = 300mm
1018-▼[icon][icon][icon][icon][icon]82	30W	L = 600mm
1018-▼[icon][icon][icon][icon][icon]83	40W	L = 900mm
1018-▼[icon][icon][icon][icon][icon]84	60W	L = 1200mm
1018-▼[icon][icon][icon][icon][icon]85	120W	L = 2400mm

## Order Options

Distribution	
<b>Direct</b>	1
<b>Direct-Indirect</b>	
Up-50% / Down-50%	2
Up-30% / Down-70%	3
Up-70% / Down-30%	4
Up-20% / Down-80%	5
Up-80% / Down-20%	6

Lumen Type	
Low	1
High	2

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
6500K	4
Tunable White 2700K-6500K	5

CRI	
>80	1
>90	2
>95	3

Beam Angle	
67°	

Control		
ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2		3
DALI-2 DT8		4
DALI +		5
D4i		6
POE (Power Over Ethernet)		7



Mounting Type	
Pendant	1
Surface	2

Material Colour		
Black		1
White		2
Grey		3

Reflector Option	
XTO 20 ( 20mm Lens)	1
XTO 25 ( 25mm Lens)	2
XTO 30 ( 30mm Lens)	3
XTO 35 ( 35mm Lens)	4
XTO 40 ( 40mm Lens)	5
XTO 45 ( 45mm Lens)	6

Optics	
Lens	1
Lens + Micro Prismatic Diffuser	2

## Accessories


Product Order Code	Accessories Name	Accessories Image
1018-01  	LED PCB	
1018-02	Suspension Wire	
1018-03 	Black + Black Lens	
1018-04 	Black + Silver Lens	
1018-05 	Chrome + Black Lens	
1018-06 	Black + Gold Lens	
1018-07	Micro Prismatic Diffuser	
1018-08	Profile Connector	
1018-09 	Profile Endcap	

## Order Options

### Lumen Type

Low	1
High	2

### CCT (Colour Temperature)

3000K	1
4000K	2
5700K	3
6500K	4
Tunable White 2700K-6500K 	5

### CRI

>80	1
>90	2
>95	3

### Material Colour

Black 	1
White 	2
Grey 	3

### Reflector Option

XTO 20 ( 20mm Lens)	1
XTO 25 ( 25mm Lens)	2
XTO 30 ( 30mm Lens)	3
XTO 35 ( 35mm Lens)	4
XTO 40 ( 40mm Lens)	5
XTO 45 ( 45mm Lens)	6