


**XTO ROUND
LINEAR**

divinity lights



**XTO ROUND
LINEAR LENS**



**XTO ROUND LINEAR
LENS + DIFFUSER**

Lens

Micro Prismatic
Diffuser



divinity lights

Quick Info

CRI ≥ 80/ 90/ 95

3000K/ 4000K/ 5700K/ 6500K

Tunable White 2700K-6500K

Up to 100lm/W

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 / DALI-2 DT8 / D4i / DALI +

POE (Power Over Ethernet)

SDCM<3

Lens

L70 @ 50,000h


Aluminium

Types

Pendant/ Surface


Single Line Diagram

XTO 20



Ø56

XTO 25




Ø56

XTO 30




Ø70

XTO 35




Ø70

XTO 40



Ø90

XTO 45



Ø90



XTO ROUND LINEAR

XTO Round Linear has :


- Range of size/angle design solutions
- Surface powder coated
- Luminaire housing of extruded aluminium
- LED PCB mounted on insert design with heat sink
- UGR less than 9
- Micro-structure & anti-glare optical lens design
- Bottom opening for easy maintenance
- Modular design concept
- Uniform illumination
- Energy-efficient LED with color rendering

Colours



Light Distribution

Direct



CRI ≥ 80/ 90/ 95



TUNABLE
WHITE 95

XTO ROUND LINEAR



XTO ROUND LINEAR (DIRECT)

Product Order Code	System Power	Dimensions
1020-1[icon]81	8W	L = 300mm
1020-1[icon]82	16W	L = 600mm
1020-1[icon]83	24W	L = 900mm
1020-1[icon]84	35W	L = 1200mm
1020-1[icon]85	70W	L = 2400mm

XTO ROUND LINEAR (DIRECT-INDIRECT)

Product Order Code	System Power	Dimensions
1020-▼[icon]81	15W	L = 300mm
1020-▼[icon]82	30W	L = 600mm
1020-▼[icon]83	40W	L = 900mm
1020-▼[icon]84	60W	L = 1200mm
1020-▼[icon]85	120W	L = 2400mm

Order Options

Distribution	
Direct	1
Direct-Indirect	
Up-50% / Down-50%	2
Up-30% / Down-70%	3
Up-70% / Down-30%	4
Up-20% / Down-80%	5
Up-80% / Down-20%	6

Lumen Type	
Low	1
High	2

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
6500K	4
Tunable White 2700K-6500K	5

CRI	
>80	1
>90	2
>95	3

Beam Angle	
67°	

Control	
ON-OFF	1
ON-OFF (FLICKER FREE)	2
DALI-2	3
DALI-2 DT8	4
DALI +	5
D4i	6
POE (Power Over Ethernet)	7

Mounting Type	
Pendant	1
Surface	2

Material Colour	
Black	1
White	2
Grey	3

Reflector Option	
XTO 20 (20mm Lens)	1
XTO 25 (25mm Lens)	2
XTO 30 (30mm Lens)	3
XTO 35 (35mm Lens)	4
XTO 40 (40mm Lens)	5
XTO 45 (45mm Lens)	6

Optics	
Lens	1
Lens + Micro Prismatic Diffuser	2

Accessories


Product Order Code	Accessories Name	Accessories Image
1020-01 <input checked="" type="checkbox"/> <input checked="" type="radio"/> <input type="radio"/>	LED PCB	
1020-02	Suspension Wire	
1020-03 <input checked="" type="checkbox"/>	Black + Black Lens	
1020-04 <input checked="" type="checkbox"/>	Black + Silver Lens	
1020-05 <input checked="" type="checkbox"/>	Chrome + Black Lens	
1020-06 <input checked="" type="checkbox"/>	Black + Gold Lens	
1020-07	Micro Prismatic Diffuser	
1020-08	Profile Connector	
1020-09 <input type="checkbox"/>	Profile Endcap	

Order Options

Lumen Type

- Low 1
- High 2

CCT (Colour Temperature)

- 3000K 1
- 4000K 2
- 5700K 3
- 6500K 4
- Tunable White 2700K-6500K  5

CRI

- >80 1
- >90 2
- >95 3

Material Colour

- Black 1
- White 2
- Grey 3

Reflector Option

- XTO 20 (20mm Lens) 1
- XTO 25 (25mm Lens) 2
- XTO 30 (30mm Lens) 3
- XTO 35 (35mm Lens) 4
- XTO 40 (40mm Lens) 5
- XTO 45 (45mm Lens) 6