

**XTO  
ROUND RING**

**divinity lights**





## XTO ROUND RING

XTO Round Ring has :

- Luminaire housing of extruded aluminium
- Range of sizes and angle designs
- Application requirements in different fields
- Surface powder coated
- LED PCB mounted on insert design with heat sink
- Bottom opening for easy maintenance
- Pendant with cable suspension
- M6 bolt for M6 fastener
- Modular design with uniform illumination
- UGR less than 9
- Microstructure anti-glare optical lens
- Energy-efficient LED with color rendering

### Quick Info

CRI  $\geq 90$

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM $<3$

Lens


L70 @50,000h

Aluminium


### Types

Pendant/ Surface


### Single Line Diagram




XTO ROUND 220




XTO ROUND 310




XTO ROUND 460



XTO ROUND 660



XTO ROUND 910




### Colours



### Light Distribution

Direct Direct-Indirect



CRI  $\geq 90$



TUNABLE  
WHITE

## XTO ROUND RING



### XTO ROUND RING (DIRECT)

Product Order Code	System Power	Dimension
3011-1  1	25W	Ø = 220mm, H = 55mm
3011-1  2	35W	Ø = 310mm, H = 55mm
3011-1  3	40W	Ø = 460mm, H = 55mm
3011-1  4	50W	Ø = 660mm, H = 55mm
3011-1  5	60W	Ø = 910mm, H = 55mm












### XTO ROUND RING (DIRECT-INDIRECT)

Product Order Code	System Power	Dimension
3011-  1	25W	Ø = 220mm, H = 55mm
3011-  2	35W	Ø = 310mm, H = 55mm
3011-  3	40W	Ø = 460mm, H = 55mm
3011-  4	50W	Ø = 660mm, H = 55mm
3011-  5	60W	Ø = 910mm, H = 55mm

## Order Options

<b>Distribution</b>	
Direct	1
Direct-Indirect	
Up-50% / Down-50%	2
Up-30% / Down-70%	3
Up-70% / Down-30%	4
Up-20% / Down-80%	5
Up-80% / Down-20%	6
<b>CCT (Colour Temperature)</b>	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4
<b>CRI</b>	
>90	1
<b>Beam Angle</b>	
67°	
<b>Control</b>	
ON-OFF	1
ON-OFF (FLICKER FREE)	2
DALI-2 DT6	3
DALI-2 DT8	4
DALI +	5
<b>Mounting Type</b>	
Pendant	1
Surface	2
<b>Material Colour</b>	
Black	1
White	2
Grey	3
<b>Reflector Option</b>	
XTO 20 ( 20mm )	1
XTO 25 ( 25mm )	2
XTO 30 ( 30mm )	3
XTO 35 ( 35mm )	4
XTO 40 ( 40mm )	5
XTO 45 ( 45mm )	6

## Accessories

Product Order Code	Accessories Name	Accessories Image
3011-01 	LED PCB	
3011-02	Suspension Wire	
3011-03 	Black + Black Lens	
3011-04 	Black + Silver Lens	
3011-05 	Chrome + Black Lens	
3011-06 	Black + Gold Lens	

## Order Options

### CCT (Colour Temperature)

3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4

### CRI

>90	1
-----	---

### Reflector Option

XTO 20 ( 20mm )	1
XTO 25 ( 25mm )	2
XTO 30 ( 30mm )	3
XTO 35 ( 35mm )	4
XTO 40 ( 40mm )	5
XTO 45 ( 45mm )	6