

XTO SQUARE

Direct | Pendant





XTO SQUARE in customised Square Luminaire in a sleek design and with Extruded aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Micro structure & antiglare optical lens design with uniform illumination and UGR less than 16. Range of Reflector width/size and angle design available.

FOR 600 X 600MM SQUARE

Available in Square shape with length 600mm and width 600mm, this fixture is crafted for direct and uniform light distribution making it ideal for professional applications. Customisations in RAL finish, Reflector finish, Wattages, and Dimensions available as per request to enhance installation and functionality.

Single Line Diagram



XTO SQUARE



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

67°

Optics

Lens

Efficacy

3000K- 85.1

4000K- 97.4

5700K- 123.5

Tunable White 2700K-6500K- 97.4

Electrical

Wattage -35W

Input Voltage- 220-240 VAC

Physical Dimensions

LXW- 600mmX600mm

Height- 70mm