

# XTO SQUARE

Direct | Surface



**XTO SQUARE** in customised Square Luminaire in a sleek design and with Extruded aluminium housing and with premium powder coating finish.


Powered by high quality LED's with a binning tolerance of  $\leq 3$  SDCM and CRI  $\geq 90$ . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Micro structure & antiglare optical lens design with uniform illumination and UGR less than 16. Range of Reflector width/size and angle design available.

## FOR 1200 X 1200MM SQUARE

Available in Square shape with length 1200mm and width 1200mm, this fixture is crafted for direct and uniform light distribution making it ideal for professional applications. Customisations in RAL finish, Reflector finish, Wattages, and Dimensions available as per request to enhance installation and functionality.

## Single Line Diagram

Surface



## XTO SQUARE



## Quick Info

### Mounting Type

Surface

### Material Colour

Customize RAL available

### Protection mode

IP40

### Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

### LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI-  $\geq 90$

Life Span - L70@50000h

MacAdam -  $\leq 3$  SDCM

### Beam Angle

67°

### Optics

Lens

### Efficacy

3000K- 94.4

4000K- 117.2

5700K- 135.9

Tunable White 2700K-6500K- 117.2

### Electrical

Wattage -70W

Input Voltage- 220-240 VAC

### Physical Dimensions

LXW- 1200mmX1200mm

Height- 70mm