

XTREME 145 DUO (DAISY-S) Linear Luminaire in a sleek design with a slim Extruded aluminium housing and with premium powder coating finish.


Powered by high-quality LED's with a binning tolerance of \leq 3 SDCM and CRI \geq 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. Dual optics of high efficiency lens with 3 beam angle options of 30°/55°/65° + Micro prismatic diffuser provides uniform illumination and glare control.

With a standard size of 1200 mm length, 27 mm height and 145mm diameter, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Pendant



XTREME 145 DUO (DAISY-S)











Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle

35° 55° 65°

Optics

Lens
Opal Diffuser
Micro Prismatic Diffuser

Efficacy

3000K- 107.3 4000K- 122.9 5700K- 140.4 Tunable White 2700K-6500K- 122.9

Electrical

Wattage - 35W/4ft
Opt Wattages Available -20W/4ft, 25W/4ft, 30W/4ft
Input Voltage- 220-240 VAC

Physical

Length- 1200mm Height- 27mm Width- 145 mm

