


XTREME 70 ANTIGLARE

Direct | Surface

XTREME 70 ANTIGLARE



XTREME 70 ANTIGLARE Linear Luminaire in a sleek design with Extruded aluminium housing and with premium powder coating finish.


Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. A new concept on Louver technology available in Matt Black, Matt White, Silver & Gun Metal Glossy with high glare control and uniform illumination

With a standard size of 1200 mm length, 73 mm height and 66 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Surface



XTREME 70 ANTIGLARE



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

110°

Optics

Antiglare Reflector

Efficacy

3000K- 110.2

4000K- 118.2

5700K- 126.2

Tunable White 2700K-6500K- 118.2

Electrical

Wattage - 28W/4ft

Opt Wattages Available -15W/4ft, 20W/4ft, 25W/4ft

Input Voltage- 220-240 VAC

Physical

Length- 1200mm

Height- 73mm

Width- 66 mm