

# XTREM BENT 165

Direct | Pendant



## XTREM BENT 165

## XTREME BENT 165



### Quick Info

#### Mounting Type

Pendant

#### Material Colour

Customize RAL available

#### Protection mode

IP40

#### Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

#### LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI-  $\geq$  90

Life Span - L70@50000h

MacAdam -  $\leq$ 3 SDCM

#### Beam Angle

80°/ 100°

#### Optics

Opal Diffuser

Micro Prismatic Diffuser

#### Efficacy

3000K- 98.5

4000K- 112.2

5700K- 125.5

Tunable White 2700K-6500K- 112.2

#### Electrical

Wattage - 35W/4ft

Direct-Indirect -Down 35W up Side 20W /4ft

Input Voltage- 220-240 VAC

#### Physical Dimensions

Length- 1200mm

Width- 164mm

Height- 30mm

**XTREM BENT 165** Linear Luminaire with Extruded aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of  $\leq$  3 SDCM and CRI  $\geq$  90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Double Micro Prismatic diffuser provides glare control and uniform illumination.

With a standard size of 1200mm length, 164mm Width, 30mm Height, both side light distribution Down 35W, Up 20W/4ft this fixture is crafted for direct light distribution, direct-indirect distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

### Single Line Diagram

#### Pendant Mounted

#### Profile Code

SDL-9003

