



divinity lights



Quick Info

CRI ≥ 90 2700K, 3000K, 4000K

Non-Dimmable/ Dali-Dimmable SDCM<3 Clear Glass L70 @50,000h Aluminium Die-Cast

Types

Surface

Single Line Diagram











ZENITH BOLLARD

Zenith Bollard fixture has:

- Luminaire housing of Aluminium
- IP66, High Ingress Protection against dust & moisture
- Flicker free operation for eye protection
- Energy-efficient LED with high colour rendering
- The built quality ensures long and maintenance free service life
- Optimum for every outdoor space including society parks, streets, educational institutes, and pathways
- Garden & pathway luminaires create pleasant light distribution with a high degree of visual comfort
- LED bollard, designed to provide radially symmetric light emission of 360



CRI ≥ 90

divinity lights

ZENITH BOLLARD

UNPUT VOLTAGE 24V DC IP66	CRI ≥ 90	
Product Order Code	System Power	Dimensions
1840	10W	Dia=150mm H=560mm

Order Options

CCT (Colour Temperature)		
2700K		
3000K		
4000K		
CRI		
>90		
Beam Angle		
360°		
Control		
Non-Dimmable	NOT Classifie	
Dali-Dimmable		
Mounting Type		
Surface		

Material Colour

Grey

263